



p . r . o . f . i . v . e

fanless solutions

APPLICATIONS

Designed for fanless applications, the Panel Board F15 single board computer finds its field of work in stationary and mobile devices.

- Rugged Industrial Systems
- Medical Solutions
- Automatic Control Panels
- Information Systems
- On-site Acquisition of Information
- Measurement & Quality Control
- Realtime Flow Control
- Public Terminal

Panel Board F15



- ▶ Powered by proven technology with support for Intel® Pentium® M and Celeron® M processor up to 1,4 GHz
- ▶ Supports up to 2 GB DDR2 memory
- ▶ The Mobile Intel® 915GME Express Chipset integrates graphic functions to support DVI-I and 18-bit LVDS interface
- ▶ Onboard touch panel controller for 4- or 8-wire touch screens
- ▶ Onboard AC'97 codec with Line IN, Aux IN, Micro IN, Line OUT and SPDIF OUT
- ▶ Intel® ICH7M I/O controller for overall interface solution
- ▶ Up to 4 PCI Express® lanes and a 32-bit PCI™ interface are supported
- ▶ Two Serial ATA ports, up to eight USB ports and two COM ports on board
- ▶ Gigabit Ethernet, SM and LPC bus for communication and control
- ▶ Connectors for daughter board solution available
- ▶ Design, Production and Support "Made in Germany"

E.E.P.D. Electronic Equipment Produktion & Distribution GmbH
Gewerbering 3 • 85258 Weichs - Germany
Telefon +49 8136 2282-0 • Telefax +49 8136 2282-109
Internet: www.eepd.de Email: sales@eepd.de

E.E.P.D. 
"Tomorrow's Technology Today"



p . o . f . i . v . e

specifications

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby.

Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS

E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury.


All mentioned trademarks are registered trademarks of their owner.

© 2009 by E.E.P.D. GmbH. All rights reserved.

October 2009 - Version 1e

Panel Board F15

CPU	Intel® Celeron® M processor 600 MHz / 512 KB cache Intel® Celeron® M processor 1.0 GHz / 512 KB cache Intel® Pentium® M processor 1.4 GHz / 2 MB cache
Chipset	Mobile Intel® 915GME / 910GMLE Express Chipset with Intel® ICH7M
BIOS	Award BIOS from Phoenix
Max. memory	Up to 2 GB DDR2 memory supports 400 MHz and 533 MHz FSB
PCI Express® Mini Card	Up to 2 PCI Express® Mini Cards One prepared with SIM card reader
PCI Express® lanes	Up to 4 PCI Express® lanes
32-bit PCI™ bus	Yes
Serial ATA interfaces	2
Parallel ATA interface	1
10/100 Mbit Ethernet	Yes (Option)
Gigabit Ethernet	Yes (Option)
LPC interface	Yes
SM bus	Yes
USB 2.0 ports	Up to 8
COM ports	2
DVI-I	Yes (DVI and Analog VGA)
LVDS interface	Yes, 18-bit dual channel LVDS with backlight connector
CRT connector	Yes (instead of DVI-I connector)
Serial DVO interface	Yes, over Board-to-Board connector
Sound	Onboard AC'97 codec
Health monitoring and management	Controllable fan, hardware monitoring, backlight control and Watchdog
Power supply	8 V - 20 V single supply, EMI filters on board optional battery solution
Touch controller	Yes, supports 4- and 8-wire touch panels
Max. operating temperature	0°C to +60°C ambient or 0°C to +70°C at any point on the surface
Max. storage temperature	-20°C to +100°C
Fanless	Designed for fanless operation
Size approx.	135 mm x 180 mm



E.E.P.D. Electronic Equipment Produktion & Distribution GmbH
Gewerbering 3 • 85258 Weichs - Germany
Telefon +49 8136 2282-0 • Telefax +49 8136 2282-109
Internet: www.eepd.de Email: sales@eepd.de

E.E.P.D. 
"Tomorrow's Technology Today"