



p . r . o . f . i . v . e

module solutions

APPLICATIONS


The P15 COM Express® was designed as an entry level board with an excellent price/performance ratio, powered by proven Intel® technology.

The P15 COM Express® finds its field of work in desktop and mobile devices.

- Rugged Industrial Systems
- Medical Solutions
- Automatic Control Panels
- Information Systems
- Measurement & Quality Control
- Realtime Flow Control
- Public Terminal

P15 COM Express®

COM  **Express®**



- ▶ Powered by proven technology including the Intel® Pentium® M and Celeron® M processors
- ▶ Up to six PCI Express® lanes and a 32-bit PCI™ interface are supported
- ▶ Full PCI Express® and PCI™ compatible CPU module
- ▶ The Mobile Intel® 915GME Express Chipset integrates graphic functions to support Analog VGA, Serial DVO and LVDS display interfaces
- ▶ Special features for industrial applications have been integrated into the PROFIVE® P15 BIOS

- ▶ Supports up to 2 GB DDR2 memory
- ▶ Two Serial ATA interfaces, one Parallel ATA interface and eight USB 2.0 ports are on board
- ▶ Works with standard carrier board according to PICMG® COM Express® specification
- ▶ Additional Ethernet connectivity options and AC'97 interface
- ▶ The PROFIVE® P15 is ready to support various operating systems
- ▶ Design, Production and Support "Made in Germany"

E.E.P.D. Electronic Equipment Produktion & Distribution GmbH
Gewerbering 3 • 85258 Weichs - Germany
Telefon +49 8136 2282-0 • Telefax +49 8136 2282-109
Internet: www.eepd.de Email: sales@eepd.de

E.E.P.D. 
"Tomorrow's Technology Today"



p . o . f . i . v . e

specifications

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby.

Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS

E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury.

All mentioned trademarks are registered trademarks of their owner.

© 2009 by E.E.P.D. GmbH. All rights reserved.

December 2009 - Version 1d

P15 COM Express®

CPU	Intel® Pentium® M and Celeron® M processor support up to 2.0 GHz
Chipset	Mobile Intel® 915GME Express Chipset
COM Express® pin out	Type 2 version
Max. memory	Up to 2 GB DDR2 memory support
PCI Express® lanes	Up to 6 PCI Express® lanes
32-bit PCI™ bus	Yes
Serial ATA interfaces	2
Parallel ATA interface	1
10/100 Mbit Ethernet	Yes (Option)
Gigabit Ethernet	Yes (Option)
LPC interface	Yes
SM bus	Yes
USB 2.0 ports	8
Analog VGA port	Yes
LVDS interface	Yes
Serial DVO interface	Yes, shared with PCI Express® graphics interface
PCI Express® graphics interface	Yes, shared with Serial DVO interface
Sound	AC'97 interface
Max. operating temperature	0°C to +60°C ambient or 0°C to +70°C at any point on the surface
Max. storage temperature	-20°C to +100°C
Type	COM Express® Basic module
Size approx.	125 mm x 95 mm

